

WHAT IS CLAIMED IS:

1 ~~1.~~ A method of controlling hand over in a mobile communication
2 system, in which a received level of a perch channel signal received at
3 a mobile station for deciding a range of a cell (or sector) is compared
4 with a reference value, to judge timing of starting or ending hand
5 over, comprising the steps of:
6 correcting said reference value using a correction value
7 prepared in advance, such that hand over is started when the mobile
8 station arrives at a range in which said mobile station can
9 communicate with a base station that covers a destination cell (or
10 destination sector), and the hand over is ended when said mobile
11 station comes out of a range in which said mobile station can
12 communicate with a base station that covers a source cell (or source
13 sector) of the hand over; and
14 judging timing of starting or ending said hand over, using
15 said reference value corrected.

1 2. A method of controlling hand over in a mobile communication
2 system, in which a received level of a perch channel signal received at
3 a mobile station for deciding a range of a cell (or sector) is compared
4 with a reference value, to judge timing of starting or ending hand
5 over, comprising the steps of:
6 preparing a correction value in advance for each combination
7 of a source cell (or source sector) and a destination cell (or destination
8 sector) of hand over;

9 recognizing a combination of a source cell (or source sector)
10 and a destination cell (or destination sector) as objects of hand over to
11 be started or ended;

12 correcting said reference value using a correction value
13 prepared in advance for said combination recognized; and

14 judging timing of starting or ending of said hand over using
15 said reference value corrected.

1 3. The method of controlling hand over according to Claim 2,
2 wherein:

3 with respect to each combination of a source cell (or source
4 sector) and a destination cell (or destination sector) of hand over, said
5 correction value is decided depending on a difference between

6 a received level of a perch channel signal of said source cell
7 (or source sector) at a point where said received level of the perch
8 channel signal of the source cell (or source sector) becomes equal to a
9 received level of a perch channel of said destination cell (or
10 destination sector).

11 and

12 a received level of the perch channel signal of said source cell
13 (or source sector) or said destination cell (or destination sector) at a
14 point where a received level of a traffic channel signal at said source
15 cell (or source sector) and a received level of a traffic channel signal
16 at said destination cell (or destination sector) become equal.

1 4. The method of controlling hand over according to Claim 2,
2 wherein:

3 with respect to each combination of a source cell (or source

5. A method of controlling hand over in a mobile communication system, in which a received level of a perch channel signal received at a mobile station for deciding a range of a cell (or sector) is compared with a reference value, to judge timing of starting or ending hand over, comprising the steps of:

- accumulating at least one result (success or failure) of judging said timing using said reference value for each combination of a source cell (or source sector) and a destination cell (or destination sector) of hand over;
- correcting said reference value depending on said accumulated result; and
- setting said corrected reference value as a new reference value that is used in judging timing of starting or ending hand over with respect to said combination again.

3 a mobile station for deciding a range of a cell (or sector) is compared
 4 with a reference value, to judge timing of starting or ending hand
 5 over, comprising the steps of:

6 accumulating at least one result (success or failure) of judging
 7 said timing using said reference value for each combination of a
 8 source cell (or source sector) and a destination cell (or destination
 9 sector) of hand over; and

10 adjusting a transmitting level of a perch channel of a base
 11 station covering a source cell (or source sector) or a destination cell
 12 (or destination sector) of a combination concerned, depending on the
 13 accumulated result.

1 7. A base station controller that judges timing of starting or
 2 ending hand over by comparing a received level of a perch channel
 3 signal with a reference value, with said perch channel signal being
 4 received at a mobile station and used for deciding a range of a cell (or
 5 sector), comprising:

6 a storage unit that stores a correction value for each
 7 combination of a source cell (or source sector) and a destination cell
 8 (or destination sector) of hand over;

9 an acquiring unit for acquiring information from a mobile
 10 station, said information indicating a combination of a source cell
 11 (or source sector) and a destination cell (or destination sector) of hand
 12 over to be started or ended with respect to said mobile station;

13 a correcting unit that corrects said reference value using a
 14 correction value that is stored in said storage unit correspondingly to
 15 the combination of the source cell (or source sector) and the
 16 destination cell (or sector), with said combination being recognized

17 from the information acquired by said acquiring unit; and
18 a timing judgement unit that uses the reference value
19 corrected by said correcting unit, to judge timing of starting or ending
20 the hand over to be started or ended with respect to said mobile
21 station.

1 ~~8.~~ A base station controller that judges timing of starting or
2 ending hand over by comparing a received level of a perch channel
3 signal with a reference value, with said perch channel signal being
4 received at a mobile station and used for deciding a range of a cell (or
5 sector), comprising:
6 an acquiring unit for acquiring information from a mobile
7 station, said information indicating a combination of a source cell
8 (or source sector) and a destination cell (or destination sector) of hand
9 over to be started or ended with respect to said mobile station;
10 a timing judgement unit that uses said reference value to
11 judge timing of starting or ending the hand over with respect to said
12 mobile station; and
13 a correcting unit that accumulates at least one result (success
14 or failure) of trying starting or ending the hand over according to the
15 timing judged by said timing judgement unit for the combination of
16 the source cell (or source sector) and the destination cell (or
17 destination sector) indicated by the information acquired by said
18 acquiring unit, corrects said reference value depending on said
19 accumulated result, and sets said corrected reference value as a new
20 reference value that is used by said timing judgement unit for judging
21 timing of starting or ending the hand over with respect to said
22 combination again.

1 9. A base station controller that judges timing of starting or
2 ending hand over by comparing a received level of a perch channel
3 signal with a reference value, with said perch channel signal being
4 received at a mobile station and used for deciding a range of a cell (or
5 sector), comprising:

6 an acquiring unit for acquiring information from a mobile
7 station, said information indicating a combination of a source cell
8 (or source sector) and a destination cell (or destination sector) of hand
9 over to be started or ended with respect to said mobile station;

10 a timing judgement unit that uses said reference value to
11 judge timing of starting or ending the hand over with respect to said
12 mobile station; and

13 an adjusting unit that accumulates at least one result (success
14 or failure) of trying starting or ending the hand over according to the
15 timing judged by said timing judgement unit for the combination of
16 the source cell (or source sector) and the destination cell (or
17 destination sector) indicated by the information acquired by said
18 acquiring unit, and adjust a transmitting level of a perch channel
19 signal of a base station that covers the source cell (or source sector) or
20 the destination cell (or destination sector) of said combination,
21 depending on said accumulated result.

1 10. A mobile terminal that judges timing of starting or ending
2 hand over by comparing a received level of a perch channel signal
3 with a reference value, with said perch channel signal being used for
4 deciding a range of a cell (or sector), comprising:

5 a storage unit that stores a correction value for each
6 combination of a source cell (or source sector) and a destination cell

8 a recognizing unit that recognizes a source cell (or source
9 sector) and a destination cell (or destination sector) of hand over to be
10 started or ended, based on received levels of perch channel signals;

15 a timing judgement unit that uses the reference value
16 corrected by said correcting unit, to judge timing of starting or ending
17 said hand over to be started or ended.

3 a notifying unit that notifies a result (success or failure) of
4 trying starting or ending the hand over according to the timing
5 judged by said timing judgement unit, to a base station with which
6 said mobile terminal is communicating.